

1. Product name:

ELIOTTIS PINE PLYWOOD C+/C

2. Manufacturer:

VARIOUS MILL IN BRAZIL

3. Certifications and credentials:

EN 13986:2004 + A1:2015 CE Marking System 4 for Non Structural uses

FSC MIX

REACH compliant

EUTR compliant

4. General characteristics

Composition	Softwood plywood bonded with phenolic resin
Wood species	Slash Pine / Loblolly Pine (pinus elliottii / pinus taeda)
Bond quality	Bonding Class 3 to EN 314-1/2 (phenolic)
Release of formaldehyde	E1

5. Veneer grades:

Layer	Finishing	Knots and knotholes	Splits
Face	Smooth	Repaired	Repaired, up to 20 mm
Back	Rough	No limitation	Occasionally up to 25mm
Inner Plies		Laps and gaps limited to 50mm in width	

6. Dimensional tolerances (EN 315):

Thickness (mm)	7	9,0	12,5	15,0	18,0	20,0	21,0	22,0	24,0	25,0	27,0	30,0
Number of layers	3	3	5	5	7	7	7	7	9	9	9	11
Maximum thickness (mm)	8,0	10,1	13,7	16,3	19,3	21,4	22,4	23,5	25,5	26,6	28,6	31,7
Minimum thickness (mm)	6,4	8,3	11,7	14,2	17,1	19,0	20,0	20,9	22,9	23,9	25,8	28,7
Typical calibrated thickness	6,7	8,5	12,6	14,3	17,3	19,4	20,7	21,7	23,5	24,6	26,3	29,5
Length and width	+0 / -3.0 mm											
Square	1.0 mm/m											

7. Standard sizes and panels per bundle:

Panel size	Bundle type	7	9,0	12,5	15,0	18,0	20,0	21,0	22,0	24,0	25,0	27,0	30,0
2500 x 1250	Standard	128	100	75	60	50	45	43	40	38	36	32	30
2440 x 1220	Standard	128	100	75	60	50	45	43	40	38	36	32	30

8. Packaging

Panels stacked over wooden skids and tied with 5 or more steel straps.
T&G bundles also include plywood side and corner protections.

9. Packaging template



10. FACE veneer example pictures:



11. BACK veneer example pictures:

